

Networked Amplifiers, At a Glance

MANUFACTURER, WEBSITE	MODEL	CHANNELS	WATTS PER CHANNEL	BRIDGED OPERATION?	FREQ. RESP (HZ)
Ashly Audio, www.ashly.com	ne8250	8	150 @ 8Ω; 250 @ 4Ω,	500 @ 8Ω	20-20k, ±1 dB
Ashly Audio	ne8250.pe	8	150 @ 8Ω; 250 @ 4Ω,	500 @ 8Ω	20-20k, ±1 dB
CAMCO, www.camcoaudio.com	Vortex 6	2	2,300 @ 4Ω; 1,350 @ 8Ω	6,600 @ 4Ω; 4,600 @ 8Ω	20-20k, ±0.15 dB
CAMCO	Vortex 4	2	1,570 @ 4Ω; 930 @ 8Ω	4,600 @ 4Ω; 3,140 @ 8Ω	20-20k, ±0.15 dB
CAMCO	Vortex 2.6	2	860 @ 4Ω; 480 @ 8Ω	2,800 @ 4Ω; 1,720 @ 8Ω	20-20k, ±0.15 dB
Crest Audio, www.crestaudio.com	Ci™ 30x4	4	100 @ 4Ω; 300 @ 8Ω; 300 @ 70-volt x4	300 @ 8Ω x2; 400 @ 140-volt x2	5-20k, ±1 dB
Crest Audio	Ci™ 20x8	8	150 @ 4Ω; 200 @ 8Ω; 200 @ 70-volt	300 @ 8Ω x4; 400 @ 140-volt x4	5-20k, ±1 dB
Crest Audio	CK100s	2	90 @ 4Ω; 60 @ 8Ω	180 @ 8Ω	10-20k, +0/-0.2 dB
Crest Audio	CK1200s	2	175 @ 4Ω; 120 @ 8Ω	350 @ 8Ω	10-20k, +0/-0.2 dB
Crest Audio	CK1400s	2	320 @ 4Ω; 255 @ 8Ω	510 @ 8Ω	10-20k, +0/-0.2 dB
Crest Audio	CK1800s	2	670 @ 4Ω; 440 @ 8Ω	880 @ 8Ω	10-20k, +0/-0.2 dB
Crown, www.crownaudio.com	I-T4000	2	2,000 @ 4Ω; 1,250 @ 8Ω	3,600 @ 4Ω; 4,000 @ 8Ω	20-20k, ±0.25 dB
Crown	I-T6000	2	3,000 @ 4Ω; 1,500 @ 8Ω	5,000 @ 4Ω; 6,000 @ 8Ω	20-20k, ±0.25 dB
Crown	I-T8000	2	4,000 @ 4Ω; 2,100 @ 8Ω	7,000 @ 4Ω; 8,000 @ 8Ω	20-20k, ±0.25 dB
Crown	Macro-Tech 5000i	2	2,000 @ 4Ω; 1,250 @ 8Ω	3,600 @ 4Ω; 4,000 @ 8Ω	20-20k, ±0.25 dB
Crown	Macro-Tech 9000i	2	3,000 @ 4Ω; 1,500 @ 8Ω	5,000 @ 4Ω; 6,000 @ 8Ω	20-20k, ±0.25 dB
Crown	Macro-Tech 12000i	2	4,000 @ 4Ω; 2,100 @ 8Ω	7,000 @ 4Ω; 8,000 @ 8Ω	20-20k, ±0.25 dB
Crown	XTi 1000	2	500 @ 4Ω; 275 @ 8Ω	1,400 @ 4Ω; 1,000 @ 8Ω	20-20k, +0/-1 dB
Crown	XTi 2000	2	800 @ 4Ω; 475 @ 8Ω	2,000 @ 4Ω; 1,600 @ 8Ω	20-20k, +0/-1 dB
Crown	XTi 4000	2	1,200 @ 4Ω; 650 @ 8Ω	3,200 @ 4Ω; 2,400 @ 4Ω	20-20k, +0/-1 dB
Dynacord, www.dynacord.de	Power H2500	2	1,200 @ 4Ω; 600 @ 8Ω	3,800 @ 4Ω; 2,900 @ 8Ω	10-30k, ±1 dB
Dynacord	Power H5000	2	2,100 @ 4Ω; 1,050 @ 8Ω	7,000 @ 4Ω; 5,000 @ 8Ω	10-30k, ±1 dB
Electro-Voice, www.electrovoice.com	TG-5	2	1,200 @ 4Ω; 600 @ 8Ω	No	10-30k, ±1 dB
Electro-Voice	TG-7	2	2,100 @ 4Ω; 1,050 @ 8Ω	7,000 @ 4Ω; 5,000 @ 8Ω	10-30k, ±1 dB
Lab.gruppen, www.labgruppen.com	PLM10000Q	2 in/4 out	2,300 @ 4Ω; 1,300 @ 8Ω	No	20-20k, ±0.05 dB
Lab.gruppen	FP+10000Q	4	2,100 @ 4Ω; 1,300 @ 8Ω	5,000 x2 @ 4Ω; 4,200 x2 @ 8Ω	6.8-34k, +0/-3 dB
Lab.gruppen	FP+7000	2	2,800 @ 4Ω; 1,450 @ 8Ω	7,000 @ 4Ω; 5,600 @ 8Ω	6.8-34k, +0/-3 dB
MC², www.mc2audio.co.uk	T 1000	2	500 @ 4Ω	1,380 @ 4Ω; 1,000 @ 8Ω	20-20k, ±0.5 dB
MC²	T 1500	2	750 @ 4Ω	2,250 @ 4Ω; 1,500 @ 8Ω	20-20k, ±0.5 dB
MC²	T 2000	2	1,000 @ 4Ω	3,000 @ 4Ω; 2,000 @ 8Ω	20-20k, ±0.5 dB
MC²	T 4-250	4	250 @ 4Ω	800 @ 4Ω; 500 @ 8Ω	20-20k, ±0.5 dB
Nexo, www.nexo-sa.com	NXAmp4x1	4	900 @ 4Ω x4; 600 @ 8Ω x4	Bridgeable 2x2, specs N/A	10-20k, ±0.5 dB
Nexo	NXAmp4x4	4	3,300 @ 4Ω x4; 1,900 @ 8Ω x4	Bridgeable 2x2, specs N/A	10-20k, ±0.5 dB
Powersoft, www.powersoft-audio.com	Digam K20	2	5,200 @ 4Ω; 2,700 @ 8Ω	18,000 @ 4Ω; 10,400 @ 8Ω	20-20k, ±0.2 dB
Powersoft	Digam K10	2	4,000 @ 4Ω; 2,000 @ 8Ω	12,000 @ 4Ω; 8,000 @ 8Ω	20-20k, ±0.2 dB
Powersoft	Digam K8	2	3,000 @ 4Ω; 1,500 @ 8Ω	9,600 @ 4Ω; 6,000 @ 8Ω	20-20k, ±0.2 dB
Powersoft	Digam K6	2	2,500 @ 4Ω; 1,300 @ 8Ω	7,200 @ 4Ω; 5,000 @ 8Ω	20-20k, ±0.2 dB
Powersoft	Digam K4	2	1,700 @ 4Ω; 900 @ 8Ω	5,200 @ 4Ω; 3,400 @ 8Ω	20-20k, ±0.2 dB
Powersoft	Digam K3	2	2,600 @ 4Ω; 1,400 @ 8Ω	N/A	5-20k, ±0.2 dB
QSC, www.qsc.com	PL325	2	850 @ 4Ω; 500 @ 8Ω	2,500 @ 4Ω; 1,700 @ 8Ω	20-20k, ±0.2 dB
QSC	PL340	2	1,250 @ 4Ω; 800 @ 8Ω	4,000 @ 4Ω; 2,600 @ 8Ω	20-20k, ±0.2 dB
QSC	PL380	2	2,500 @ 4Ω; 1,500 @ 8Ω	8,000 @ 4Ω; 5,000 @ 8Ω	20-20k, ±0.2 dB
Turbosound, www.turbosound.com	RackDP50	4	1,250 @ 2Ω	Yes, output spec N/A	5-30k, ±1 dB
Yamaha, www.yamahaca.com	TX6n	2	3,000 @ 4Ω; 1,800 @ 8Ω	6,000 @ 4Ω or 8Ω	10-20k, ±0.5 dB
Yamaha	TX5n	2	2,200 @ 4Ω; 1,300 @ 8Ω	5,000 @ 4Ω; 4,400 @ 8Ω	10-20k, ±0.5 dB
Yamaha	TX4n	2	1,900 @ 4Ω; 1,100 @ 8Ω	4,400 @ 4Ω; 3,800 @ 8Ω	10-20k, ±0.5 dB
Yamaha	T5n	2	2,350 @ 4Ω; 1,350 @ 8Ω	5,000 @ 4Ω; 4,700 @ 8Ω	20-20k, +0/-0.5 dB
Yamaha	T4n	2	2,050 @ 4Ω; 1,150 @ 8Ω	4,400 @ 4Ω; 4,100 @ 8Ω	20-20k, +0/-0.5 dB
Yamaha	T3n	2	1,400 @ 4Ω; 750 @ 8Ω	3,800 @ 4Ω; 2,800 @ 8Ω	20-20k, +0/-0.5 dB

	NETWORK FUNCTIONS	MSRP	S/N RATIO	INPUT CONNECTORS	OUTPUT CONNECTORS	NETWORKING NOTES
	C=Control, M=Monitoring, A=Audio					
	C/M/A	\$1,890	>98 dB	Euroblock	Euroblock	CobraNet option
	C/M/A	\$2,610	>98 dB	Euroblock	Euroblock	CobraNet option, onboard Protea DSP
	C/M/A	\$4,995	>110 dB (A)	XLR w/thru	Speakon	Options: DSP, CobraNet, EtherSound
	C/M/A	\$3,775	>110 dB (A)	XLR w/thru	Speakon	Options: DSP, CobraNet, EtherSound
	C/M/A	\$2,995	>110 dB (A)	XLR w/thru	Speakon	Options: DSP, CobraNet, EtherSound
	C/M/A	\$2,283	>97 dB (A)	Euroblock	Barrier strip	Options: Crest NexSys, MediaMatrix or CobraNet
	C/M/A	\$1,695	>97 dB (A)	Euroblock	Barrier strip	Options: Crest NexSys, MediaMatrix or CobraNet
	C/M/A	\$960	>105 dB (A)	Euroblock	Barrier strip	Options: Crest NexSys, MediaMatrix or CobraNet
	C/M/A	\$1,040	>105 dB (A)	Euroblock	Barrier strip	Options: Crest NexSys, MediaMatrix or CobraNet
	C/M/A	\$1,200	>105 dB (A)	Euroblock	Barrier strip	Options: Crest NexSys, MediaMatrix or CobraNet
	C/M/A	\$1,420	>105 dB (A)	Euroblock	Barrier strip	Options: Crest NexSys, MediaMatrix or CobraNet
	C/M/A	\$5,050	>105 dB (A)	XLR w/thru, AES/EBU	Binding post, Speakon	Audio via HiQnet
	C/M/A	\$6,179	>105 dB (A)	XLR w/thru, AES/EBU	Binding post, Speakon	Audio via HiQnet
	C/M/A	\$7,762	>105 dB (A)	XLR w/thru, AES/EBU	Binding post, Speakon	Audio via HiQnet
	C/M/A	\$4,255	>110 dB (A)	XLR w/thru	Binding post, Speakon	Audio via HiQnet
	C/M/A	\$5,200	>110 dB (A)	XLR w/thru	Binding post, Speakon	Audio via HiQnet
	C/M/A	\$6,855	>110 dB (A)	XLR w/thru	Binding post, Speakon	Audio via HiQnet
	C/M/A	\$827	100 dB (A)	XLR w/thru	Binding post, Speakon	All via HiQnet; onboard DSP
	C/M/A	\$1,151	100 dB (A)	XLR w/thru	Binding post, Speakon	All via HiQnet; onboard DSP
	C/M/A	\$1,607	100 dB (A)	XLR w/thru	Binding post, Speakon	All via HiQnet; onboard DSP
	C/M/A	\$3,840	111 dB (A)	XLR w/thru	Binding post, Speakon	Via IRIS-Net option; DSP optional
	C/M/A	\$4,590	109 dB (A)	XLR w/thru	Binding post, Speakon	Via IRIS-Net option; DSP optional
	C/M/A	\$3,840	109 dBA	XLR w/thru, Euro, opt AES/EBU	Binding post, Speakon	Via IRIS-Net option; DSP optional
	C/M/A	\$4,590	111 dBA	XLR w/thru, Euro, opt AES/EBU	Binding post, Speakon	Via IRIS-Net option; DSP optional
	C/M/A	N/A	>114 dB	XLR w/thru, AES/EBU	Binding post or Speakon	Onboard Dolby Lake DSP
	C/M	\$6,495	>112 dB (A)	XLR w/thru	Binding post or Speakon	
	C/M	\$5,095	>112 dB (A)	XLR w/thru	Binding post or Speakon	
	C/M (audio opt.)		105 dB	XLR or Euroblock	Speakon	Ti Bridge adds CobraNet or EtherSound
	C/M (audio opt.)		105 dB	XLR or Euroblock	Speakon	Ti Bridge adds CobraNet or EtherSound
	C/M (audio opt.)		105 dB	XLR or Euroblock	Speakon	Ti Bridge adds CobraNet or EtherSound
	C/M (audio opt.)		105 dB	XLR or Euroblock	Speakon	Ti Bridge adds CobraNet or EtherSound
	C/M/A	\$4,600	105 dB	XLR w/thru	Speakon	EtherSound module option
	C/M/A	\$9,200	105 dB	XLR w/thru	Speakon	EtherSound module option
	C/M		>110 dB	Combo XLR/TRS	Speakon	Ethernet control/SmartCard setting storage
	C/M		>110 dB	Combo XLR/TRS	Speakon	Ethernet control/SmartCard setting storage
	C/M		>109 dB	Combo XLR/TRS	Speakon	Ethernet control/SmartCard setting storage
	C/M		>108 dB	Combo XLR/TRS	Speakon	Ethernet control/SmartCard setting storage
	C/M		>108 dB	Combo XLR/TRS	Speakon	Ethernet control/SmartCard setting storage
	C/M		>112 dB	Combo XLR/TRS	Speakon	Ethernet control/SmartCard setting storage
	C/M/A	\$1,649	106 dB	XLR w/thru	Binding post and Speakon	Using optional RAVE unit; DSP optional
	C/M/A	\$2,149	105 dB	XLR w/thru	Binding post and Speakon	Using optional RAVE unit; DSP optional
	C/M/A	\$3,599	104 dB	XLR w/thru	Binding post and Speakon	Using optional RAVE unit; DSP optional
	C/M	\$TBA	110 dB (A)	XLR w/thru	Speakon	Onboard DSP
	C/M/A	\$5,699	108 dB (DIN)	XLR w/thru, AES/EBU	Binding post and Speakon	CobraSound/EtherSound optional; onboard DSP
	C/M/A	\$5,199	107 dB (DIN)	XLR w/thru, AES/EBU	Binding post and Speakon	CobraSound/EtherSound optional; onboard DSP
	C/M/A	\$4,799	106 dB (DIN)	XLR w/thru, AES/EBU	Binding post and Speakon	CobraSound/EtherSound optional; onboard DSP
	C/M	\$3,799	107 db (DIN)	XLR or Euroblock	Binding post or Speakon	
	C/M	\$2,999	106 dB (DIN)	XLR or Euroblock	Binding post or Speakon	
	C/M	\$2,399	105 dB (DIN)	XLR or Euroblock	Binding post or Speakon	