

BGW**Products****News & Articles****About BGW****Tech. Support**

Amplifiers
Computers
Subwoofers
Product Info
Specification

- M1100
- M1100T
- M2200
- M2200T

Racks & Rack Mount Acc.

**Subwoofers****M1100****Specifications****BGW M1100 Specifications**

Power	1400 Watts IHF 950 Watts Continuous
Amplifier Class	AB+B (low quiescent)
Usable Frequency Response	25Hz to 180Hz
Maximum Output (1m)	>124dB SPL above 40Hz
Electronic Crossover (Linkwitzriley filters)	SwitchSet(TM) 24dB/octave frequencies selectable at 63, 71, 80, 89, 100, 112, 125, 140, 160, and 180Hz
Summing Amp	Electronically sums dual inputs to mono
High Pass Output	Post-summing amp single ended output on barrier strip, follows crossover setting
Sensitivity	Adjustable from -10dBm to +16dBm (0.24 5V to 5.0V) with hi-rel locking shaft control
Input Limiting	Active above +16dBm
Remote Power-On	Contact closure or 15VDC, opto-isolated
Power Requirements	50-60Hz, 100-120 VAC, 15 AMps max, 8 Amps nominal; or 220-240VAC 8 Amps, 4 Amps nominal; with universal voltage transformer
Cabinet Construction	¾-inch void free baltic birch plywood, carpet wrapped with stacking corner protectors
Grille	14 gauge perforated steel
Electronics Module	19 x 19 inches, with 72CFM fan mounted over amplifier heatsink
Fan Control	Variable speed, off at idle

Dimensions

Inches (HxWxD)	27.875 x 32.75 x 28.6
Centimeters (HxWxD)	70.8 x 83.2 x 72.7
Net Weight	190 lbs (81.7 kg)
ProNet Price	

\$ 2,995.00

[Back to Top](#)



13130 Yukon Avenue, Hawthorne, CA 90250 USA
800-HOT-AMPS (468-2677); FAX: (310) 676-6713
e-mail: info@bgw.com or sales@bgw.com
[BGW Terms, Conditions and Policies](#)

design & hosting

