

FSM-17RK **17" RACKMOUNT FLAT SCREEN LCD MONITOR**



FEATURES

- 17" TFT/LCD Flatpanel
- 1280x1024 resolution, supporting 16.7 million colors
- Plugs directly into VGA output
- Extra wide viewing angle
- Space saving, 3.0" depth

The **FSM-17RK, FLAT SCREEN LCD MONITOR** is the perfect match for any VTM Series Multi-format On Screen Monitor or other multimedia devices such as editors and data servers. A 17" TFT active matrix LCD panel supporting up to 1280x1024 resolution with 16.7 million display colors is housed in a 9RU ultra-thin 3" deep space saving rackmount. The FSM-17RK is VGA/SVGA/XGA compatible with a flicker and static free extra wide viewing angle that is low on power consumption and high in display solutions.

DISPLAY

17" (Diagonal) viewable, TFT active matrix, flat panel

RESOLUTION:

1280x1024 @ 60Hz, optimum

FREQUENCY:

Horizontal: 15-80 kHz

Vertical: 50-77Hz

BRIGHTNESS:

250 cd/m2, typical

CONTRAST RATIO:

500:1

VIEWING ANGLE:

85° horizontal and vertical

INPUT

INPUT SIGNAL:

Video: Analog RGB

Connector: 15-pin D-sub (VGA)

Sync: H and V separate (TTL),
sync-on-green (0.3 Vp-p)

Sync Frequency:

Horizontal: 15 to 63 kHz

Vertical: 50 to 77 Hz

ON-SCREEN CONTROLS

Brightness, contrast

Clock, phase

Auto Adjust

Color Temperature

H & V position and size

OSD

Mode Recall

Backlight

Auto sleep

POWER

INPUT:

12 ± 0.5 VDC / 4.58 A

CONSUMPTION:

54 W max.

ENVIRONMENTAL

OPERATING TEMPERATURE:

0° to 50° C

STORAGE TEMPERATURE:

-20 to 45 degrees C

HUMIDITY:

10% to 80%, non-condensing

MECHANICAL

Height: 15.75" (40.0 cm)

Width: 19" (48.3 cm)

Depth: 3" (7.6 cm)

Weight: 14.1 lb. (6.4 kg)

STANDARD ACCESSORIES

Operator's Manual

Power adapter AC to DC 100-240 VAC
to 12 VDC@5A max.

1-year limited warranty on flat panel
display