

## Model 4022 Industrial DVD Player Specifications

### Benefits

- Rugged construction
- Compact design
- Easy to install and operate
- Automatically plays
- Automatically loops
- Skips menus
- Skips commercials

### Uses

- Digital signage - retail
- Displays - museums & galleries
- POP displays
- Industrial audio/video systems
- Interactive kiosks
- Hospitals & doctors offices
- Senior or child facilities

### FEATURES

- Composite video, component video, and S-Video outputs
- Supported disc formats: 80mm and 120mm CD-R/RW, DVD-S, DVD-D, DVD±R/RW,
- Supported media: DVD-VIDEO, CDDA, VCD, PHOTO CD, SVCD, DVCD, Standard Audio CD, MP3 CD
- Wireless remote control and slow motion playback
- Stereo analog audio outputs
- Switching power supply protects against surges
- Private labeling available
- Support both NTSC/PAL DVD video discs on playback
- Zoom-in function on displayed images
- Progressive scan 2x,4x,8x,16x,32x
- Slow scan 1/2, 1/4 and 1/8 speed

### PACKAGE CONTENTS

- DVD player
- Switching power supply, DC 12v/3.5A
- Standard 6' / 3 prong power cord
- A/V cable (component video and right/left audio)
- Remote control (1 remote shipped with every 4 players)

### SPECIFICATIONS

Final specifications are subject to change without notice based on market availability.

System Type Digital Video Player

Video Format MPEG-2 DVD

Image Resolutions

- Component video: 480i / 480P.
- Composite video: NTSC /60Hz/ 525 lines. PAL/50Hz/625 lines.
- Dimensions 10"(L) x 8"(W) x 3 1/4"(H)
- Power Supply - switching 100-240V, 47-63Hz
- 120VAC current draw 12.5 Watts
- Temperature : operating 10°C - 40°C
- Temperature : storage -20°C - 40°C
- Humidity: Operating - 20% to 80% RH (non condensing)
- Humidity: Storage - 5% to 90% RH (non condensing)



## Model 4022 Industrial DVD Player Pictures

